



**FEATURES**

- QUIK-START™ ON/OFF switch
- 115 VAC, single phase operation
- Central lubrication system
- 37 ft (11.3 m) extension cord w/GFI
- Adjustable industry type attachments

**SG12E LEGACY SERIES SINGLE HEAD SURFACE GRINDER**

The SG12E Legacy Series Surface Grinder was designed for use by both seasoned contractors and DIY homeowners, alike. And, unlike many similar sized machines, it operates from and readily available 15 ampere, 115 VAC, single phase power source that can be found on almost every jobsite. The operator handle quickly folds making it easier to transport in today's smaller SUV vehicles. Handle height is also adjustable to better reduce operator back strain. The exclusive QUIK-STOP™ motor switch stops the unit when the handle grip is released to enhance operator safety and control. A 37 foot extension cord complete with integral GFI is provided as a standard accessory to help address less than favorable jobsite conditions. The SG12E accommodates a wide range of industry-standard, interchangeable attachments including Legacy Series grinding stones, scarifiers, the SCRAPE-R-TACH™ Coatings Removal System, the DIAM-A-TACH™ Diamond Grinding System and Pro Polish™ Concrete Floor Polishing System for unmatched versatility and productivity.

**SPECIFICATIONS**

<b>Power Source</b>	1.5 HP (1.1 kw), 115 VAC, 60 HZ, 1 phase
<b>Frame</b>	Unitized, welded steel plate
<b>Drive System</b>	Single V-belt/pulley reduction
<b>Multi-Accessory Disc Configuration</b>	One each, aluminum, 12 inch (305 mm) diameter, direct attachment mount with plastic wedges
<b>Nominal Disc Rotation Speed</b>	250 RPM
<b>Dust Port Connection</b>	3 inch (76 mm) diameter
<b>Dimensions</b>	Width: 19-3/4" (502 mm) Operator handle width: 28-1/2" (724 mm) Height: 40-1/2" (1029 mm), maximum extension Length: 28" (711 mm), handle folded Length: 39" (991 mm), operating configuration
<b>Weight</b>	242 lbs (110 kg)

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.