

## **CX8C Combi rollers**



## **TECHNICAL DATA MASSES**

Max. operating mass	8400 kg
Operating mass (incl. ROPS)	7600 kg
Module mass (front/rear)	4150 kg/3450 kg

## **COMPACTION**

Split drums	Yes
Centrifugal force (high/low amplitude)	74/54 kN
Nominal amplitude (high/low)	0.6/0.3 mm
Static linear load	27.7 kg/cm
Vibration frequency (high/low amplitude)	44/53 Hz
Water tank volume	385 I
Emulsion tank	385 I

## **TRACTION**

Speed range	0-12 km/h
Vertical oscillation	±6°
Max. theoretical gradeability	41 %

- Operator station -slidable & full rotation
- Touch screen display -moves with the seat
  Short machine below 4 m for easy
- handlingUp to 1200 mm drum offset



### **ENGINE**

Manufacturer/Model	Deutz TD 3.6 Stage V/T4f
Туре	Water cooled turbo diesel
Rated power, SAE J1995	55 kW (74.0 hp ) @ 2200 rpm
Fuel tank capacity	105 I

## **HYDRAULIC SYSTEM**

Driving	Axial piston pump with variable displacem. Rad. piston motors(4) with variable displacem. Flow divider
Vibration	Axial piston pumps (1) with variable displacement. Axial piston motors (1) with constant dispacement.
Steering	Load sensing system. Gear pump with constant displacement.
Service brake	Hydrostatic in forward and reverse lever.
Parking/ Emergency brake	Failsafe multidisc brake in both drums.

#### Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all information's are supplied without liability.




## **CX8C Combi rollers**



# DIMENSIONS

### **DIMENSIONS**

A. Wheelbase	2870 mm
B1. Width, front	1620 mm
C. Curb clearance	720 mm
D. Drum diameter	1120 mm
H1. Height, with ROPS/cab	2990 mm
K. Ground clearance	270 mm
L. Length	4038 mm
O. Off-set	1200 mm
O1. Overhang, right	85 mm
O2. Overhang, left	85 mm
R2. Turning radius, inside	2650 mm
S. Drum shell thickness	17 mm
W1. Drum width	1500 mm
W2. Width, wheel module	1454 mm
W3. Width, tyre	285 mm
W4. Wheel track	463 mm
W5. Wheel spacing	60 mm



### **OPTIONAL EQUIPMENT**

Air Conditioning /Automatic Climate Control (ACC) (Optional)

- The system contains fluorinated greenhouse gases.
- Coolant designation: HFC-134a
- Coolant weight when full: 1,35 kg
- CO<sub>2</sub>-equivalent: 1,930 ton
   GWP: 1430

#### Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all information's are supplied without liability.