

DRP25DReversible plates



TECHNICAL DATA

N/A	A	0	0		C
IVI	H	O	J	ᆮ	J

Basic mass 257 kg
Operating mass 260 kg

COMPACTION

 Amplitude
 1.4 mm

 Centrifugal force
 40 kN

 Frequency
 80 Hz

TRACTION

Max. gradeability 32 % Max. working speed 27 m/min

ENGINE

Manufacturer/Model Hatz 1B20
Emissions according to EU Stage V/non US EPA
Type Air cooled diesel
Number of cylinders 1
Fuel tank capacity 3.0 I
Power 3.1 kW @ 3000 rpm
Fuel consumption I /h, avg 0.7 l/h

DRIVE SYSTEM

Drive system Mechanical

Find us locally at www.dynapac.com


We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.




DRP25D **Reversible plates**



DIMENSIONS





DIMENSIONS

H. Height	700 mm
H1. Height, steering rod (lowered)	1030 mm
H2. Height, steering rod (raised)	1150 mm
L. Length	1405 mm
L1. Length	762 mm
W. Basic plate width	600 mm

STANDARD FEATURES

- Control handle with vibration isolation
- Height adjustable control lever
 Control lever lock in transport and working Block paving mat
- position
- Reverse drive protection
- Highly wear resistant base plate
- All around protection hood
 All around protection for V-belt
 Automatic decompression
 One point lift
 Recoil starter

- Electric starter
- Hour meter

OPTIONAL EQUIPMENT

- Puncture proof transport wheels (+5kg)
- Service Kit

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.