



## TECHNICAL DATA

### MASSES

Max. operating mass	500 kg
Transport mass	220 kg

### DIMENSIONS

Length, max	2000 mm
Transport dimensions (LxWxH)	1670 x 1000 x 1100 mm
Working width, max.	1000 mm
Working width, min.	250 mm

### MATERIAL HOPPER

Capacity	150 l
----------	-------

### TRACTION

Max. working speed	30 m/min
Transport speed, max	3.5 km/h

### ENGINE

Manufacturer/Model	Honda GXV 160
Emissions according to	EPA
Rated power	3.2 kW
Type	Air cooled gasoline
Number of cylinders	1
Fuel tank capacity	5 l

### DRIVE SYSTEM

Drive system	Hydrostatic
--------------	-------------

### UNDERCARRIAGE

Front wheels	2x hydrostatically driven wheels, 400 mm diameter
Rear wheels	1x swivel castor wheel, 260 mm diameter

### STANDARD FEATURES

- Two hydrostatically driven wheels and a swivel castor wheel
- Forward and reverse drive controls at operator handle
- Layer thickness control with independent left and right hydraulic cylinders
- Operating width control with hydraulically controlled hatches
- Screed heated with exhaust gas recovery
- Hopper container
- Parking brake

Find us locally at [www.dynapac.com](http://www.dynapac.com)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.